



MEET+ 10-U3

USB PTZ Camera for Middle and Small Meeting Room

To Make Collaboration Easy and Affordable
 Meet+ 10-U3 is ideal used for video conferencing in the middle and small meeting room. It is equipped with 1/2.8" sensor and high quality 10X optical lens, to output crisp images with realistic color, even in low light or high contrast of brightness and darkness via 3.0 port. USB 3.0 can output different resolutions, up to 1080p60.
 It works with any of your favorite conferencing software, totally plug and play, and user-friendly.

10X | 1080P60
POWER VIA USB 3.0 PORT




1080p60 FHD output

Equipped with advanced image processing, cutting-edge algorithms, a 1/2.8-inch sensor, and a high-quality lens, it outputs crystal clear images up to 1080p60 FHD resolution.



10X optical zoom

Uses truly 10X optical zoom lens, with 62.5-degree wide angle FOV, fast and accurate focus performance to capture details in large and middle room.



Plug and play

USB3.0 video output 1080p60 resolution, plug and play, work with any of your favorite video conferencing software.



Power via USB 3.0 port

Meet+ 10-U3 can power via a USB 3.0 port directly, with no need for the power supply adaptor, which makes deployment even more simple, a single cable enables power, video, and control.



Quiet and smooth PTZ movement

Thanks to the compact and sophisticated mechanism design, and accurate driven algorithms, Meet+ 10-U3 can move very smoothly without noise at variable pan/tilt/zoom speed.



Easy installation and control

Meet+ 10-U3 is plug and play—no driver needed. Simply open your favorite live streaming or video conferencing platform, and control it with the remote control, the software, or any VISCA device.



Specifications

Camera	Meet+ 10-U3
Part NO.	TLC -1000-U3-10P
Sensor	1/2.8 inch, high-quality 5MP CMOS Sony sensor
Zoom	10X optical zoom, 12X digital zoom
Lens	f= 4.7~47mm, F1.6-3.0
Horizontal View Angle	62.5°(wide)~6.43°(tele)
Vertical Viewing Angle	40.1°~ 4.1°
Diagonal Viewing Angle	69.7°~7.56°
Minimum Working Distance	Wide: 0.5m; Tele: 1m
S/N Ratio	≥50dB

Video Format	USB 3.0:
	YUY2: 1920*1080P60; 1280*720P60; 1024*576P60; 640*480P60; 640*360P60
	USB 2.0:
	YUY2: 1280*720P25; 1024*576P30/25; 640*480P50/30/25; 640*360P60/50/30/25

Image Parameters

Noise Reduction	2D/3D
Minimum LUX	0.7lux(50 IRE Max AGC, 1/30, F1.8)
White Balance	Auto/Manual/Indoor/Outdoor/Push/Sodium/Fluorescent
Focus	Auto/Manual
Iris	Auto/Manual
Electronic Shutter	Auto/Manual
BLC	Supported

Mechanism

Pan Rotation Angle	-170°~+170°
Tilt Rotation Angle	-30°~+90°
Pan Rotation Speed	0°~120°/s
Titl Rotation Speed	0°~80°/s
Preset	128 presets via RS232, 10 presets via remote controller
Control	RS232/RS485/USB/Remote Controller
Video Port	USB 3.0

General

Input voltage	5V 1000mA(via USB 3.0)/DC: 12V 2A(via Power Adapter)
Power Consumption	DC: 12V 2A(Pmax=7W)
Operating Temperature	-10 C ~50 C
Operating Humidity	≤80%
Color	Silver
Camera Dimension	148mm×132mm×162mm
Package Dimension	28x24x24cm
Package Content	Camera, Remote Controller, RS232 cable, USB 3.0 cable, Power Supply



Power Supply
DC12V

Video Output
USB 3.0



Remote control port
RS232/RS485